

Replacement Information for Model FD-1500 Filter/Dryer



Table of Contents

Introduction	1	Expected Life of Desiccant in FD-1500 Replacement Cartridge.....	2
		Equilibrium Moisture Table	3

Introduction

The Becker filter/dryer is a durable unit designed to provide dry, clean instrumentation gas by removing particles, free water, and water vapor from natural gas.

The design of the FD-1500 incorporates a replaceable “Spin on” cartridge inside a carbon steel housing. Gas enters the unit from the top and continues around the narrow passageway between the housing and the cartridge increasing the velocity of the gas. The gas enters the cartridge from the bottom resulting in a complete change in direction of the flow. This change in direction in gas flow causes the free water to separate from the gas. A three-inch space between the bottom of the housing and the cartridge allows for collection of free water. The gas then enters the replaceable cartridge. The replacement cartridge has three main components:

1. A primary filter to remove larger particles.
2. 2 lbs. of silica gel (desiccant) which can absorb 1 lb. of water vapor and free water.
3. A secondary fine filter with 110 square inches of media to strain particles as small as 10 microns.

The FD-1500 provides adequate capacity to flow sufficient gas for instrumentation. The maximum operating pressure is 1500 psig (each FD-1500 is hydrostatically tested to 2250 psig). The flow capacity of the entire unit is 50 scfm due to the fittings, etc. The capacity of the fine filter itself at 1500 psig and 10 psid differential pressure is 212 scfm.

The FD-1500 will provide reliable use if the following replacement procedure for the cartridge is observed.

Technical Assistance

Should you have any questions, you may contact your local Becker sales representative or Becker technical assistance at:

Dresser, Inc.

Becker Control Valves
Attn: Technical Assistance
1550 Greenleaf Avenue
Elk Grove Village, IL 60007
Toll Free: (800) 323-8844
Tel: (847) 437-5940
Fax: (847) 437-2549
Email: becker@dresser.com
www.dresser.com

Table 1 - Equilibrium Moisture Contents of Natural Gases Above the Critical Temperature

PSIA											
°F	14.7	100	200	300	400	500	600	700	800	900	1000
-40	9.10	1.50	0.88	0.66	0.55	0.49	0.44	0.41	0.39	0.37	0.36
-36	11.5	1.90	1.10	0.80	0.68	0.59	0.54	0.50	0.47	0.45	0.43
-32	14.4	2.40	1.30	0.99	0.82	0.72	0.65	0.60	0.57	0.54	0.51
-28	17.8	2.90	1.60	1.20	1.00	0.87	0.79	0.72	0.68	0.64	0.61
-24	22.0	3.60	2.00	1.50	1.20	1.10	0.95	0.87	0.81	0.77	0.73
-20	27.0	4.40	2.40	1.80	1.50	1.30	1.10	1.00	0.97	0.92	0.87
-16	33.1	5.40	3.00	2.20	1.80	1.50	1.40	1.20	1.20	1.10	1.00
-12	40.5	6.50	3.60	2.60	2.10	1.80	1.60	1.50	1.40	1.30	1.20
-8	49.3	7.90	4.30	3.10	2.50	2.20	1.90	1.80	1.60	1.50	1.50
-4	59.8	9.50	5.20	3.70	3.00	2.60	2.30	2.10	1.90	1.80	1.70
0	72.1	11.4	6.20	4.50	3.60	3.10	2.70	2.50	2.30	2.10	2.00
4	86.8	13.7	7.40	5.30	4.30	3.60	3.20	2.90	2.70	2.50	2.40
8	104	16.4	8.80	6.30	5.10	4.30	3.80	3.40	3.20	3.00	2.80
12	124	19.5	10.5	7.50	6.00	5.10	4.50	4.00	3.70	3.50	3.30
16	148	23.2	12.4	8.80	7.00	5.90	5.20	4.70	4.30	4.00	3.80
20	176	27.4	14.6	10.4	8.20	7.00	6.10	5.50	5.10	4.70	4.40
24	208	32.4	17.2	12.2	9.70	8.20	7.20	6.40	5.90	5.50	5.10
28	246	38.1	20.2	14.3	11.3	9.50	8.30	7.50	6.80	6.30	5.90
32	289	44.7	23.7	16.7	13.2	11.1	9.70	8.70	7.90	7.30	6.90
34	313	48.4	25.6	18.0	14.2	11.9	10.4	9.30	8.50	7.90	7.40
36	339	52.4	27.7	19.4	15.3	12.9	11.2	10.0	9.20	8.50	7.90
38	367	56.6	29.9	20.1	16.5	13.9	12.1	10.8	9.80	9.10	8.50
40	396	61.1	32.2	22.6	17.8	14.9	13.0	11.6	10.6	9.80	9.10

Reference: Gas Engineers Handbook 1st Edition

The Table Above Can Be Used As Follows:

Assume that the pipeline pressure is 1000 psig at 40°F. This gas can hold 9.1 lb./mmscf of water.

Assume that the pressure will be cut from 1000 psig to 100 psig at the supply regulator.

Assume that for every 100 psig drop in pressure the gas will drop 7°F in temperature. In this case, the temperature will drop from 40°F to -23°F (1000 psig - 100 psig / 100 psig x 7°F =63°F).

From the table, look up 100 psig and -23°F (or the closest value). If the number is below 7 lb./mmscf, water will fallout of the gas and the desiccant should be replaced once a year to prevent problems as a result of freezing.

The above test procedure indicates the predicted service life of the Becker FD-1500 filter/dryer cartridge assembly. Should you require any additional information or assistance please feel free to telephone using our toll free number,

1-800-323-8844.

About Dresser, Inc.

Dresser, Inc. is a leader in providing highly engineered infrastructure products for the global energy industry. The company has leading positions in a broad portfolio of products, including valves, actuators, meters, switches, regulators, piping products, natural gas-fueled engines, retail fuel dispensers and associated retail point-of-sale systems, and air and gas handling equipment. Leading brand names within the Dresser portfolio include Dresser Wayne® retail fueling systems, Waukesha® natural gas-fired engines, Masoneilan® control valves, Consolidated® pressure relief valves, and Roots® blowers. It has manufacturing and customer service facilities located strategically worldwide and a sales presence in more than 100 countries.

While this information is presented in good faith and believed to be accurate, Becker Control Valves, Dresser, Inc. does not guarantee satisfactory results from reliance upon such information. Nothing contained herein is to be construed as a warranty or guarantee, expressed or implied, regarding the performance, merchantability, fitness or any other matter with respect to the products, nor as a recommendation to use any product or process in conflict with any patent. Becker Control Valves, Dresser, Inc. reserves the right, without notice, to alter or improve the designs or specifications of the products described herein.

Dresser, Inc.

1550 Greenleaf Avenue
Elk Grove Village, IL 60007
Tel: (847) 437-5940
Fax: (847) 437-2549
www.dresser.com/becker



©2009 Dresser, Inc. All rights reserved.